



ALTV244175UL, ALTV244175ULCB UL Listed AC CCTV Power Supply

Rev. DSALTV244175UL - B16F

Overview



- These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via four (4) fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV244175UL

- Four (4) fuse protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV244175UL3

ALTV244175UL w/3-wire
Line Cord.

ALTV244175ULCB

- Four (4) Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

ALTV244175ULCB3

ALTV244175ULCB w/3-wire
Line Cord.

Specifications

- Input 115VAC, 50/60Hz, 2.7 amp.
 - 24VAC @ 7 amp (170VA) or 28VAC @ 6.25 amp (175VA) supply current.
 - Main fuse rated @ 10 amp/250V.
 - Illuminated power disconnect circuit breaker with manual reset.
 - Surge suppression.
 - AC power LEDs.
 - Spare fuse(s) provided (all models w/primary and/or secondary fuses).
 - Unit maintains camera synchronization.
 - Ease of installation saves time and eliminates costly labor.
- Product weight:
 - ALTV244175UL: 10.8 lbs.
 - ALTV244175UL3: 11.1 lbs.
 - ALTV244175ULCB: 10.8 lbs.
 - ALTV244175ULCB3: 11.1 lbs.
 - Shipping weight:
 - ALTV244175UL: 11.5 lbs.
 - ALTV244175UL3: 11.8 lbs.
 - ALTV244175ULCB: 11.5 lbs.
 - ALTV244175ULCB3: 11.8 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions

12.25"H x 7.75"W x 4.5"D

