

**TA-4600**



- Overhead Door Contact
- 18" Armoured Cable
- Universal Magnet for Flexibility in mounting
- Standard Gap 3"
- Cast Aluminium Casings for Harsh Environments
- Closed Loop

**TA-4106T-BR**



- Side mounted Concealed terminals
- Closed Loop
- Standard gap up to 1 1/4"
- Spacers, Covers and Screws Included

**TA-4105-WT**



- Mini Stick-On Contact with Flange
- Standard Gap: 1 1/8" (25mm)
- Centre Leads
- Closed Loop
- 18" Leads
- Adhesive and Screw Mount

**TA-4104D-WT**



- Mini Stick-On Contact With Flange
- Standard Gap: 1 1/4" (28mm)
- Side Leads
- Closed Loop
- 18" Leads
- Adhesive and Screw Mount

**TA-4102DT-WT**



- 3/8" Hole, Press to Fit
- Quick Terminals
- Closed Loop

### TA-4103-WT or BR



- 3/4" Hole, Press to Fit
- Standard 18" Leads
- Self-Locking
- Solid, One Piece Design
- Standard 1" Gap on Steel Door
- Closed Loop

### TA-4103T-WT or BR



- 3/4" Hole, Press to Fit
- Quick Terminals
- Self-Locking
- Standard 1" Gap on Steel
- Closed Loop

### TA-4107D-BR and TA-4108D-BR



- 1" Hole Press to fit
- Self-Locking
- Standard 1" Leads
- UI/ULC Listed
- SPDT (TA-4107D)  
DPDT (TA-4108D)

### TA-4160



- UL Listed
- 1" gap on S.P.D.T.
- Easy Install Replaces standard ANSI Stainless Steel Door Plate
- Optimum Concealment Application
- 36" Jacketed Cable Lead, Custom Lengths Available
- Convert Installation Enhances Resistance to Tampering or Compromise